

JT/24

系列自动泵 AUTOMATIC BOOSTER PUMPS

JT/24 Series automatic booster system are suitable for distributing water under pressure in residential housing and small-scale agricultural application. Their special operating system makes them an appropriate solution in all cases where water flow rates do not ensure suitable operating pressures. Reliable, safe and simple to use.

JT/24该系统可以提供家用及工业用途所需的恒压自动供水，为用户提供足够用水，安全可靠，使用方便。

JT/24 COMPONENTS

- Water pump
- 24Liters horizontal tank with membrane
- 50cm or 25cm flexible hose is available as requests
- Adjustable pressure switch (Preset at 1.4~2.8)
- Pressure gauge
- 1.5m supply cable with schuko plug

WORKING CONDITIONS

Max temperature of fluid up to 40°C
Max pressure 10bar
Max ambient temperature 40°C

工作条件：

最高流体温度40°C
最大可承受压力10bar
最高环境温度40°C
压力开关预设值1.4~2.8kg



JT/24



JT-L/24



JSW/24



JT-P/24



JT-S/24

1100 Watt

V230~50HZ
V110~60HZ

1.4 ÷ 2.8bar

流量 Q.Max
70 l/min 4200L/h

Pump with
1-Impeller

吸程 Max. Suction
9 m

1100 Watt

V230~50HZ
V110~60HZ

1.4 ÷ 2.8bar

流量 Q.Max
70 l/min 4200L/h

Pump with
1-Impeller

吸程 Max. Suction
9 m

1100 Watt

V230~50HZ
V110~60HZ

1.4 ÷ 2.8bar

流量 Q.Max
70 l/min 4200L/h

Pump with
1-Impeller

吸程 Max. Suction
9 m

1100 Watt

V230~50HZ
V110~60HZ

1.4 ÷ 2.8bar

流量 Q.Max
70 l/min 4200L/h

Pump with
1-Impeller

吸程 Max. Suction
9 m